

**shaw** hard surface<sup>®</sup>

**GRAIN  
CLICK**



## Product Specifications

**tile name** grain  
**style number** 0364V  
**construction** luxury vinyl plank with In\*Step locking system

**class / ASTM F1700** class III printed film vinyl plank, type A (smooth), type B (embossed)

**nominal dimensions** 7 in wide x 48 in long  
**wearlayer thickness** 20 mil or 0.020" (0.5 mm)  
**overall thickness** 4 mm or .156 in

**actual size / ASTM F536** width: 7.28 in or 18.5 cm,  
length: 47.72 in or 121.2 cm

**backing class** commercial grade  
**finish** ExoGuard™ quartz-enhanced urethane  
**edge profile** micro bevel  
**added antimicrobial** yes, FlorSept™  
**installation recommended** floating  
**adhesive** none required, not recommended

## packaging

**square feet per carton** 24.13 sf  
**pieces per carton** 10 pcs  
**weight per carton** 33.72 lbs

**ILC sound rating ASTM E492** greater than 55 when tested over 6" concrete with ceiling plenum and approved underlayment

**slip resistance ASTM D2047**  
**static load ASTM F970**  
**flexibility ASTM F137**  
**resistance to heat ASTM F1514**  
**resistance to light ASTM F1515**  
**resistance to chemicals ASTM F925**  
**radiant panel ASTM E648**  
**nbs smoke ASTM E66**

ADA compliant  
500 psi  
passes  
passes  
passes  
passes  
class I  
less than 450


## warranty

10 year limited commercial wear warranty. Please visit [www.shawhardsurface.com](http://www.shawhardsurface.com) for the most current warranty information.


## Environmental

Indoor Air Quality - FloorScore® certified

## Métodos de Instalación:



**Ashlar**



**Stagger**