

**shaw** hard surface®

**GRAIN  
PEGADO DIRECTO**



Product Specifications

**tile name** grain  
**style number** 0502V  
**construction** luxury vinyl plank with In\*Step locking system

**class / ASTM F1700** class III printed film vinyl plank, type A (smooth), type B (embossed)

**nominal dimensions** 7 in wide x 48 in long  
**wearlayer thickness** 20 mil or 0.020" (0.5 mm)  
**overall thickness** 2.5 mm or .098 in

**actual size / ASTM F536** width: 7 in or 17.78 cm  
length: 48 in or 121.92 cm

**backing class** commercial grade  
**finish** ExoGuard™ quartz-enhanced urethane  
**edge profile** none, smooth  
**added antimicrobial** yes, FlorSept™  
**installation recommended** glue down  
**adhesive** Shaw 4100 or S150

packaging

**square feet per carton** 34.98 sf  
**pieces per carton** 15 pc  
**weight per carton** 29.32 lbs

**IIC sound rating ASTM E492** greater than 55 when tested over 6" concrete with ceiling plenum and approved underlayment

**slip resistance ASTM D2047** ADA compliant  
**static load ASTM F970** 1500 psi  
**flexibility ASTM F137** passes  
**resistance to heat ASTM F1514** passes  
**resistance to light ASTM F1515** passes  
**resistance to chemicals ASTM F925** passes  
**radiant panel ASTM E648** class I  
**nbs smoke ASTM E66** less than 450


**warranty**

10 year limited commercial wear warranty. Please visit [www.shawhardsurface.com](http://www.shawhardsurface.com) for the most current warranty information.


**Environmental**

Indoor Air Quality - FloorScore® certified

Métodos de Instalación:



**Ashlar**



**Stagger**